



# LoRaWAN Sensor Device

## Liquids Level (Pressure) & Temperature



---

### Sensors

Absolute or relative pressure sensor for leveling  
High resolution, IP67 weather resistant, piezo resistive technology  
Interface: I<sup>2</sup>C

Pressure sensor

Relative ranges: 0 ... 0.3, 0...1, -0.5...0.5, -1...3, -1...10, 0.0 ... 10 bar

Absolute ranges: 0...1, 0.5...1.5, 0...3, 0...10, 0...30, 0...100, 0...200, 0...400, 0...600, 0...1000 bar

Temperature compensated

Accuracy  $\pm 0.15\%$  of full scale

Temperature sensor

Range: -10...+80 °C, -40...+110 °C

10m cable, longer cable on request

---

### LoRaWAN specifics

Device class A

Over the air activation (OTAA)

Adaptive data rate (ADR)

Frequency bands:

EU868 MHz (EU Version), US915MHz (US Version), AS923 (Asia Version) or AU920 (Australia Version)

Input Sensitivity: -148 dBm (EU Version)

---

### Supply

Internal battery 2 x C-type Alkaline  
Integrated sensor supply

---

### Operating conditions

-30°C to 60°C  
100% RH

---

## Weight

---

250g w/o batteries

---

## Dimensions

---

LoRaWAN sensor device: 80 x 135 x 70 mm  
Sensor: 21 mm diameter, 73 mm length

---

## Enclosure

---

Weatherproof, impact and UV- resistant polycarbonate enclosure

---

## Dimensional drawings (only enclosure)

---

